Lead Free Flowbite

allen co.

March 18, 2021 - Price Sheet 21113 Flowbite fittings are a heat-free method for joining Copper, CPVC, and PEX Tube, and are

designed to save time and money on installation

- Designed for use with ASTM B88 hard drawn and annealed copper tube, type K, L, or M, in the 1/2" through 3/4" range; CPVC water tube per ASTM D2846/2846M and PEX tube that meets the requirements of ASTM F876 & F877
- Material content DZR CZ132 brass
- Operates at temperatures from 0° to 250° F at max. working pressure of 200 PSI
- Sold in bag/master quantities

Features & Benefits

- Push fit
- Reduced installation time
- Ideal for service & repair
- 1/2" and 3/4" diameter potable water systems
- "O-Ring" design for leak free seals
- EDPM O-Ring seal
- •316 stainless steel retaining ring

T (0		Sold in bag/master quantities					
Type of Service		System Operating Conditions					
Hot & cold potable water		32° F to 200° F • max. 200 PSI					
Potable water system flushing		Compliant with major plumbing codes					
Chilled water with corrosion inhibitors		0° F to 250° F • max. 200 PSI • ethylene glycol/propylene glycol-50% max.;concentration					
Hydronic heating	g	0° F to 250° F • max. 200 PSI • ethylene glycol/propy	lene glycol-50%	max.;concenti	ration		
Rainwater/greywater		32° F to 200° F + max. 200 PSI					
	Part #	Description	Bag Qty	Master Qty	Net Price (each)		
	FB12FNL	Adapter (C x F) 1/2" x 1/2"	10	100			
	FB1234FNL	Adapter (C x F) 1/2" x 3/4"	10	100			
	FB34FNL	Adapter (C x F) 3/4" x 3/4"	5	100			
	FB1FNL	Adapter (C x F) 1" x 1"	5	100			
	FB12MNL	Adapter (C x M) 1/2" x 1/2"	10	200			
	FB1234MNL	Adapter (C x M) 1/2" x 3/4"	10	200			
	FB34MNL	Adapter (C x FM 3/4" x 3/4"	5	100			
	FB1MNL	Adapter (C x M) 1" x 1"	5	100			
	FB134MNL	Reducer Adapter (C x M) 1" x 3/4"	5	100			
	FB12CNL	Cap 1/2"	10	200			
	FB34CNL	Cap 3/4"	5	150			
	FB38CNL	Cap 3/8"	5	150			
	FB1CNL	Cap 1"	5	200			
	FB12CONL	Coupling 1/2" x 1/2"	10	150			
	FB34CONL	Coupling 3/4" x 3/4"	5	100			
	FB1CONL	Coupling 1" x 1"	5	100			
	FB38CONL	Coupling 3/8" x 3/8"	5	100			
	FB1238CONL	Coupling 1/2" x 3/8"	5	100			
	FB3412CONL	Reducer Coupling 3/4" x 1/2"	5	100			
	FB134CONL	Reducer Coupling 1" x 3/4"	5	100			
	FB1290NL	Elbow 90° 1/2" x 1/2"	10	150			
	FB3490NL	Elbow 90° 3/4" x 3/4"	5	80			
	FB3890NL	Elbow 90° 3/8" x 3/8"	5	80			
	FB190NL	Elbow 90° 1" x 1"	5	50			
	FB341290NL	Reducing Elbow 90° 3/4" x 1/2"	5	80			
A	FB1290DENL	Drop Ear 90° Elbow (C x F) 1/2"	10	100			



800.433.9228 fax: 216.932.6067

E-mail: allencompany@sbcglobal.net www.allenco.us

	Part #	Description	Bag Qty	Master Qty	Net Price (each)
	FB12TNL	Tee 1/2"	10	100	
	FB34TNL	Tee 3/4"	5	50	
	FB38TNL	Tee 3/8"	5	50	
	FB1TNL	Tee 1"	5	50	
	FB343412TNL	Tee 3/4" x 3/4" x 1/2"	5	50	
	FB341234TNL	Tee 3/4" x 1/2" x 3/4"	5	50	
	FB341212TNL	Tee 3/4" x 1/2" x 1/2"	5	50	
	FB1112TNL	Tee 1" x 1" x 1/2"	5	50	
	FB1134TNL	Tee 1" x 1" x 3/4"	5	50	
	FB1341TNL	Tee 1" x 3/4" x 1"	5	50	
223	FB12RTNL	Removal Tool 1/2"	5	500	
	FB34RTNL	Removal Tool 3/4"	5	250	
	FB1RTNL	Removal Tool 1"	5	200	
	FB12BVNL	Ball Valve 1/2"	10	10	
	FB34BVNL	Ball Valve 3/4"	10	10	
	FB1BVNL	Ball Valve 1"	6	6	
	FB34MBVNL	Male X Ball Valve 34"	1	50	
9 6	FB1238ASTOPNL	1/2" Flowbite x 3/8" OD Comp Angle 1/4 Turnstop	1	200	
	FB1238SSTOPNL	1/2" Flowbite x 3/8" OD Comp Straight 1/4 Turnstop	1	200	
	FBWHC1234-18NL	1/2" Flowbite x 3/4" FIP Water Heater Connector - 18"	1	50	
	FBWHC3434-18NL	1/2" Flowbite x 3/4" FIP Water Heater Connector - 18"	1	25	
5	FB3434WHCBV-18NL	1/2" Flowbite x 3/4" FIP Water Heater Connector - 18"	1	25	



800.433.9228 fax: 216.932.6067 E-mail: allencompany@sbcglobal.net www.allenco.us